

AMENDMENTS TO THE CLAIMS

Claims 1-24 (Cancelled)

- OK to enter
(PM) 03/07/06
25. (Previously Presented) A memory device comprising:
a main memory array;
an internal processor to execute programming code; a hidden storage area coupled
with the main memory array, wherein the programming code prevents
access to the hidden storage area if a password is invalid; and
a bad password counter coupled with the internal processor to maintain a record
of one or more invalid passwords.
26. (Previously Presented) The memory device of claim 25, wherein the main
memory array comprises a non-volatile writable memory array.
27. (Currently Amended) The memory device of claim 26, wherein the non-volatile
writable memory array comprises one or more of the following: a flash memory
array, a battery backed memory array, and a polymer memory array.
28. (Original) The memory device of claim 25, wherein the hidden storage area
comprises one or more hidden memory banks.
29. (Currently Amended) The memory device of claim 28, wherein the hidden
memory banks are divided into one or more user spaces and a password space
containing one or more stored valid reference passwords.
30. (Currently Amended) The memory device of claim 29, wherein the valid
password allows ~~accesses~~ access to one of the user spaces.
31. (Original) The memory device of claim 28, wherein the hidden memory banks
include a swap space to copy data between the hidden memory banks without
exposing the data in the hidden memory banks.

32. (Original) The memory device of claim 28, wherein the hidden storage area further comprises a bank selector to select a hidden memory bank.
33. (Original) The memory device of claim 28, wherein the hidden storage area further comprises an output bus gate to prevent access to the hidden memory banks.
34. (Original) The memory device of claim 33, wherein the hidden storage area further comprises an address decoder to open the output bus gate when provided the valid password.
35. (Currently Amended) The memory device of claim 33, wherein the hidden storage further comprises an address decoder to open the output bus gate when a valid memory address within the hidden memory banks is provided.

Claims 36-39 (Cancelled)

40. (Previously Presented) A method, comprising:
storing one or more valid passwords in a hidden memory area;
receiving a password at an internal processor coupled with the hidden memory area;
executing programming code to verify the password against a valid reference password stored within the hidden memory area; and
maintaining a record of one or more invalid passwords at a bad password counter coupled with the internal processor.
41. (Original) The method of claim 40, further comprising permitting access to read from the hidden memory area if the password is verified.
42. (Original) The method of claim 40, further comprising permitting access to write to the hidden memory area if the password is verified.

43. (Original) The method of claim 40, further comprising permitting access to write to the hidden memory area if a valid address in the hidden memory area is provided.
44. (Currently Amended) The method of claim 40, further comprising dividing the hidden memory area into one or more of user spaces, a password space, and a swap space.
45. (Currently Amended) The method of claim 40, further comprising writing a recovery password that allows ~~a~~the bad password counter to be reset.
46. (Currently Amended) The method of claim 40, further comprising writing a system administrator password that allows the hidden memory area contents to be reset.
47. (Original) The method of claim 40, further comprising writing a system administrator password that allows a recovery password to be reset.
48. (Currently Amended) The method of claim 40, further comprising writing a system administrator password that allows ~~a~~the bad password counter to be reset.
49. (Previously Presented) A machine-readable medium having stored thereon data representing sets of instructions which, when executed by a machine, cause the machine to:
- store one or more valid passwords in a hidden memory area;
- receive a password at an internal processor connected to the hidden memory area;
- execute programming code to verify the password against a valid reference password stored within the hidden memory area; and
- maintain a record of one or more invalid passwords at a bad password counter coupled with the internal processor.

50. (Previously Presented) The machine-readable medium of claim 49, wherein the sets of instructions which, when executed by the machine, further cause the machine to read from the hidden memory area if the password is verified.
51. (Previously Presented) The machine-readable medium of claim 49, wherein the sets of instructions which, when executed by the machine, further cause the machine to write to the hidden memory are if the password is verified and a valid address in the hidden memory is provided.
52. (Currently Amended) The machine-readable medium of claim 49, wherein the sets of instructions which, when executed by the machine, further cause the machine to divide the hidden memory area into one or more of user spaces, a password space, and a swap space.
53. Cancelled
54. (Previously Presented) The machine-readable medium of claim 49, wherein the sets of instructions which, when executed by the machine, further cause the machine to write a system administrator password that allows hidden memory area content to be reset.

Claims 55-56 (Cancelled)

57. (Currently Amended) A system comprising:
- a wireless communication transceiver; and
 - a memory device coupled to the wireless ~~communications~~ communication transceiver, the memory device including
 - a main memory array,
 - an internal processor to execute programming code,

a hidden storage area connected to the main memory array, wherein the programming code prevents access to the hidden storage ~~are~~ area without a valid password, and
a bad password counter coupled with the internal processor to maintain a record of one or more invalid passwords.

58. (Previously Presented) The system of claim 57, wherein the main memory array comprises a non-volatile writable memory array.
59. (Previously Presented) The system of claim 58, wherein the non-volatile writable memory array comprises one or more of the following: a flash memory array, a battery backed memory array, and a polymer memory array.
60. (Previously Presented) The system of claim 57, wherein the hidden storage area comprises one or more hidden memory banks.